



Ekspluatācijas spiediens  
Max. 16 bar  
Vielas temperatūra  
-20 °C to +100 °C  
Materiāls  
Galvanised steel / brass  
Atspere  
Stainless-steel  
Blīvējums  
NBR

## Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rate and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414. Suitable for all applications with an above-average air consumption and characterised by extreme conditions.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	SW mm
K- 07 35 12 98	4000	77.0	Stem, I.D. 10	24
K- 07 35 13 01	4000	75.3	Stem, I.D. 13	24
K- 07 35 13 02	4000	75.3	Stem, I.D. 16	24
K- 07 35 13 03	4000	74.3	Stem, I.D. 19	24