



Ekspluatācijas spiediens
Max. 12 bar, maximum static working pressure (non-pulsating)
Iespraužamo iemavu un nipeļu ekspluatācijas spiediens
0 to 35 bar
Vielas temperatūra
-20 °C to +60 °C
Korpuss, vārsta korpuss
Nickel-plated brass
Vārsts
Brass
Atbloķēšanas uzdeva
Plastic
Atspere, sprostgredzens, tapas, lodes
Stainless steel
Blīvējums
NBR

Apraksts

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	SW mm
K- 07 35 02 98	1300	55.4	G 1/4 male	22
K- 07 35 02 99	1300	55.4	G 3/8 male	22
K- 07 35 03 00	1300	58.3	G 1/2 male	24