

# K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type



Ekspluatācijas spiediens  
maks. 10 bar  
Iekšējās daļas  
Stainless steel 1.4404  
Korpuss  
Stainless steel 1.4404  
Poga, vārsts  
Stainless steel 1.4404  
Vielas temperatūra  
-20 °C to +150 °C  
Vītne  
Stainless steel 1.4404  
Blīvējums  
FKM

## Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Caurpl_de nom.<br>l/min | Garums<br>mm | Savienojums | SW<br>mm |
|----------------|-------------------------|--------------|-------------|----------|
| K- 07 35 12 76 | 1800                    | 70.5         | G 1/4 male  | 21       |
| K- 07 35 12 77 | 1800                    | 70.0         | G 3/8 male  | 21       |
| K- 07 35 12 78 | 1800                    | 72.5         | G 1/2 male  | 25       |