

K-LKM S NW7,4 DREH SCHL TUE VA

Safety couplings DN 7.4, stainless steel 1.4404, with hose stem, swivel type



Ekspluatācijas spiediens
maks. 10 bar
Iekšējās daļas
Stainless steel 1.4404
Korpuss
Stainless steel 1.4404
Poga, vārsts
Stainless steel 1.4404
Vielas temperatūra
-20 °C to +150 °C
Vītne
Stainless steel 1.4404
Blīvējums
FKM

Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	SW mm
K- 07 35 12 83	1800	88.5	Stem, I.D. 6	21
K- 07 35 12 85	1800	88.5	Stem, I.D. 9	21
K- 07 35 12 86	1800	88.5	Stem, I.D. 13	21