



Ekspluatācijas spiediens
maks. 20 bar
Vielas temperatūra
-20 °C to +100 °C
Atspere, lodes
Stainless-steel
Bīdāma uzmava
Anodised aluminium
Vārsta korpusa pieslēgums
Nickel-plated brass
Atbloķēšanas uzmava
Hardened and nickel-plated steel
Blīvējums
NBR

Apraksts

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums
K- 07 35 08 88	1400	86.0	Stem, I.D. 6
K- 07 35 12 96	1400	86.0	Stem, I.D. 8
K- 07 35 08 89	1400	86.0	Stem, I.D. 9
K- 07 35 12 97	1400	86.0	Stem, I.D. 10
K- 07 35 08 90	1400	86.0	Stem, I.D. 13