

# K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)



Tips  
A-10  
Spriegums  
8 - 30 V  
Aizsardzības veids  
IP 65 acc. to EN 60529  
Elektriskais pieslēgums  
With right-angle connector acc. to DIN EN 175301-803 A  
Izejas signāls  
4 to 20 mA, 2-wire  
Nelinearitāte  
0.5% of span  
Vides temperatūra  
0 °C to +80 °C  
Vielas temperatūra  
0 °C to +80 °C  
Daļas, kas saskaras ar mērišanas vielu  
CrNi steel 1.4404  
Korpuss  
CrNi steel 1.4404

## Apraksts

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Mērišanas diapazons | Vītnes |
|----------------|---------------------|--------|
| K- 07 20 10 46 | 0 - 1.0 bar         | G 1/4  |
| K- 07 20 10 47 | 0 - 1.6 bar         | G 1/4  |
| K- 07 20 10 48 | 0 - 2.5 bar         | G 1/4  |
| K- 07 20 10 49 | 0 - 4.0 bar         | G 1/4  |
| K- 07 20 10 50 | 0 - 6.0 bar         | G 1/4  |
| K- 07 20 10 51 | 0 - 10.0 bar        | G 1/4  |
| K- 07 20 10 52 | 0 - 16.0 bar        | G 1/4  |
| K- 07 20 10 53 | 0 - 25.0 bar        | G 1/4  |
| K- 07 20 10 54 | 0 - 40.0 bar        | G 1/4  |
| K- 07 20 10 55 | 0 - 60.0 bar        | G 1/4  |
| K- 07 20 10 56 | 0 - 100.0 bar       | G 1/4  |
| K- 07 20 10 57 | 0 - 160.0 bar       | G 1/4  |
| K- 07 20 10 58 | 0 - 250.0 bar       | G 1/4  |
| K- 07 20 10 59 | 0 - 400.0 bar       | G 1/4  |
| K- 07 20 10 60 | 0 - 600.0 bar       | G 1/4  |