



Tips
S-20
Spriegums
DC 8 ... 36 V
Aizsardzības veids
IP 65 acc. to EN 60529
Elektriskais pieslēgums
With right-angle connector acc. to DIN EN 175301-803 A
Izejas signāls
4 to 20 mA, 2-wire
Nelinearitāte
up to 0.25% of span
Vides temperatūra
-40 °C to +70 °C
Vielas temperatūra
-30 °C to +100 °C
Daļas, kas saskaras ar mērišanas vielu
CrNi steel 1.4571
Korpuss
CrNi steel 1.4571

Apraksts

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development.
Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

Produkts

Apzīmējums	Mērišanas diapazons	Vītnes
K- 07 20 12 55	-1 / 0.0 bar	G 1/2
K- 07 20 12 56	0 - 0.4 bar	G 1/2
K- 07 20 12 57	0 - 1.0 bar	G 1/2
K- 07 20 12 64	0 - 4.0 bar	G 1/2
K- 07 20 12 67	0 - 6.0 bar	G 1/2
K- 07 20 12 58	0 - 10.0 bar	G 1/2
K- 07 20 12 60	0 - 16.0 bar	G 1/2
K- 07 20 12 62	0 - 25.0 bar	G 1/2
K- 07 20 12 65	0 - 40.0 bar	G 1/2
K- 07 20 12 68	0 - 60.0 bar	G 1/2
K- 07 20 12 59	0 - 100.0 bar	G 1/2
K- 07 20 12 61	0 - 160.0 bar	G 1/2
K- 07 20 12 63	0 - 250.0 bar	G 1/2
K- 07 20 12 66	0 - 400.0 bar	G 1/2
K- 07 20 12 69	0 - 600.0 bar	G 1/2