

K-DRS W DREHBAR

Pressure switches, changeover type, turnable



Modelis
Spring-loaded diaphragm (NBR)
Pieteikums platība
Air, hydraulic oil, oil emulsions, water
Vides temperatūra
-25 °C to +85 °C
Elektriskais pieslēgums
Coupling plug Pg 9, DIN 43650
Slēgšanas biežums
200/min.
Funkcija
Changeover
Mērišanas spriegums
250 V
Materiāls
Galvanised steel

Apraksts

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērišanas spriegums V	Vītnes	Iestatišanas diapazons
K- 07 30 28 55	250	G 1/8	0,3 - 2,0 bar
K- 07 30 28 56	250	G 1/8	1,0 - 10,0 bar
K- 07 30 28 57	250	G 1/8	10,0 - 70,0 bar
K- 07 30 28 58	250	G 1/4	0,3 - 2,0 bar
K- 07 30 28 59	250	G 1/4	1,0 - 10,0 bar
K- 07 30 28 60	250	G 1/4	10,0 - 70,0 bar