

Robust diaphragm pressure gauges, connection radial on bottom

**Tips**

422.12 (robust), 432.50 (chemical)

**Modelis**

Diaphragm pressure gauge in robust design or for chemical applications

**Izmantošana**at chemical applications in aggressive environments  
for gaseous or liquid media,**Kvalitātes klase**

1,6

**Vides temperatūra**

no -20 °C līdz +60 °C

**Vielas temperatūra**

max. +100 °C

**Korpuss, gredzens**

Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)

**Mērelements**

CrNi steel

**Rādītāja mehānisms**

Copper alloy (robust type), CrNi steel (type for chemical applications)

**Skatstikls**

Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)

**Ø mērišanas atloks**

100 mm

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Ø mērišanas atloks mm	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 10 99	100	-1 / +1.5 bar	100.0	G 1/2"
K- 07 20 11 00	100	0 - 1.0 bar	100.0	G 1/2"
K- 07 20 11 01	100	0 - 1.6 bar	100.0	G 1/2"
K- 07 20 11 02	100	0 - 2.5 bar	100.0	G 1/2"
K- 07 20 11 03	100	0 - 4.0 bar	100.0	G 1/2"
K- 07 20 11 04	100	0 - 6.0 bar	100.0	G 1/2"
K- 07 20 11 05	100	0 - 10.0 bar	100.0	G 1/2"
K- 07 20 11 06	100	0 - 16.0 bar	100.0	G 1/2"
K- 07 20 11 07	100	0 - 25.0 bar	100.0	G 1/2"