



Tips

131.11

Modelis

Bourdon-tube pressure gauge, CrNi steel type

Izmantošana

For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere

Clean Dry Air applications, machine and plant construction

Kvalitātes klase

2,5

Vides temperatūra

-40 °C to +60 °C

Vielas temperatūra

max. +100 °C

Korpuss

CrNi steel

Skatstikls

Polycarbonate

Apraksts

Standard model manufactured entirely from CrNi steel, economical and reliable.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 03 82	0 - 1.0 bar	40.0	G 1/4"
K- 07 20 03 83	0 - 1.6 bar	40.0	G 1/4"
K- 07 20 03 84	0 - 2.5 bar	40.0	G 1/4"
K- 07 20 03 85	0 - 4.0 bar	40.0	G 1/4"
K- 07 20 03 86	0 - 6.0 bar	40.0	G 1/4"
K- 07 20 03 87	0 - 10.0 bar	40.0	G 1/4"
K- 07 20 03 88	0 - 16.0 bar	40.0	G 1/4"
K- 07 20 03 89	0 - 25.0 bar	40.0	G 1/4"
K- 07 20 03 90	0 - 40.0 bar	40.0	G 1/4"
K- 07 20 03 91	0 - 60.0 bar	40.0	G 1/4"
K- 07 20 03 92	0 - 100.0 bar	40.0	G 1/4"
K- 07 20 04 83	0 - 1.0 bar	50.0	G 1/4"
K- 07 20 04 84	0 - 1.6 bar	50.0	G 1/4"
K- 07 20 04 85	0 - 2.5 bar	50.0	G 1/4"
K- 07 20 04 86	0 - 4.0 bar	50.0	G 1/4"
K- 07 20 04 87	0 - 6.0 bar	50.0	G 1/4"
K- 07 20 04 88	0 - 10.0 bar	50.0	G 1/4"
K- 07 20 04 89	0 - 16.0 bar	50.0	G 1/4"
K- 07 20 04 90	0 - 25.0 bar	50.0	G 1/4"
K- 07 20 04 91	0 - 40.0 bar	50.0	G 1/4"
K- 07 20 04 92	0 - 60.0 bar	50.0	G 1/4"
K- 07 20 04 93	0 - 100.0 bar	50.0	G 1/4"