



Tips

232.30

Izmantošana

For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere

Modelis

Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)

Kvalitātes klase

1,6 (Ø 63 mm), 1,0 (Ø 100 mm)

Vides temperatūra

-40 °C to +60 °C

Vielas temperatūra

max. +200 °C

Korpuss

CrNi steel

Skatstikls

Laminated safety glass Ø 63 = Polycarbonate

Apraksts

Safety version with more fracture-resistant separating wall

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 07 15	-1 / 0.0 bar	63.0	G 1/4"
K- 07 20 07 16	0 - 1.6 bar	63.0	G 1/4"
K- 07 20 07 17	0 - 2.5 bar	63.0	G 1/4"
K- 07 20 07 18	0 - 4.0 bar	63.0	G 1/4"
K- 07 20 07 19	0 - 6.0 bar	63.0	G 1/4"
K- 07 20 07 20	0 - 10.0 bar	63.0	G 1/4"
K- 07 20 07 21	0 - 16.0 bar	63.0	G 1/4"
K- 07 20 07 22	0 - 25.0 bar	63.0	G 1/4"
K- 07 20 07 23	0 - 40.0 bar	63.0	G 1/4"
K- 07 20 07 24	0 - 60.0 bar	63.0	G 1/4"
K- 07 20 07 25	0 - 100.0 bar	63.0	G 1/4"
K- 07 20 01 97	0 - 1.0 bar	100.0	G 1/2"
K- 07 20 01 98	0 - 1.6 bar	100.0	G 1/2"
K- 07 20 01 99	0 - 2.5 bar	100.0	G 1/2"
K- 07 20 02 00	0 - 4.0 bar	100.0	G 1/2"
K- 07 20 02 01	0 - 6.0 bar	100.0	G 1/2"
K- 07 20 02 02	0 - 10.0 bar	100.0	G 1/2"
K- 07 20 02 03	0 - 16.0 bar	100.0	G 1/2"
K- 07 20 02 04	0 - 25.0 bar	100.0	G 1/2"
K- 07 20 02 05	0 - 40.0 bar	100.0	G 1/2"
K- 07 20 02 06	0 - 60.0 bar	100.0	G 1/2"
K- 07 20 02 07	0 - 100.0 bar	100.0	G 1/2"
K- 07 20 02 08	0 - 160.0 bar	100.0	G 1/2"
K- 07 20 02 09	0 - 250.0 bar	100.0	G 1/2"
K- 07 20 02 10	0 - 400.0 bar	100.0	G 1/2"