



Tips

232.50

Izmantošana

For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise

Modelis

Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel

Kvalitātes klase

1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)

Vides temperatūra

-40 °C to +60 °C

Vielas temperatūra

max. +200 °C

Korpuss

CrNi steel

Skatstikls

Laminated safety glass Ø 63 = Polycarbonate

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērīšanas diapazons	Ø mm	Savienojums
K- 07 20 06 01	-1 / 0.0 bar	63.0	G 1/4"
K- 07 20 06 02	0 - 2.5 bar	63.0	G 1/4"
K- 07 20 06 03	0 - 4.0 bar	63.0	G 1/4"
K- 07 20 06 04	0 - 6.0 bar	63.0	G 1/4"
K- 07 20 06 05	0 - 10.0 bar	63.0	G 1/4"
K- 07 20 06 06	0 - 16.0 bar	63.0	G 1/4"
K- 07 20 06 07	0 - 25.0 bar	63.0	G 1/4"
K- 07 20 06 08	0 - 40.0 bar	63.0	G 1/4"
K- 07 20 06 09	0 - 100.0 bar	63.0	G 1/4"
K- 07 20 00 36	-1 / 0.0 bar	100.0	G 1/2"
K- 07 20 00 37	-1 / +0.6 bar	100.0	G 1/2"
K- 07 20 00 38	-1 / +1.5 bar	100.0	G 1/2"
K- 07 20 00 39	-1 / +3.0 bar	100.0	G 1/2"
K- 07 20 00 40	-1 / +5.0 bar	100.0	G 1/2"
K- 07 20 00 41	-1 / +9.0 bar	100.0	G 1/2"
K- 07 20 00 42	-1 / +15.0 bar	100.0	G 1/2"
K- 07 20 00 43	0 - 1.0 bar	100.0	G 1/2"
K- 07 20 00 44	0 - 1.6 bar	100.0	G 1/2"
K- 07 20 00 45	0 - 2.5 bar	100.0	G 1/2"
K- 07 20 00 46	0 - 4.0 bar	100.0	G 1/2"
K- 07 20 00 47	0 - 6.0 bar	100.0	G 1/2"
K- 07 20 00 48	0 - 10.0 bar	100.0	G 1/2"
K- 07 20 00 49	0 - 16.0 bar	100.0	G 1/2"
K- 07 20 00 50	0 - 25.0 bar	100.0	G 1/2"
K- 07 20 00 51	0 - 40.0 bar	100.0	G 1/2"
K- 07 20 00 52	0 - 60.0 bar	100.0	G 1/2"
K- 07 20 03 10	-1 / 0.0 bar	160.0	G 1/2"
K- 07 20 03 11	-1 / +0.6 bar	160.0	G 1/2"
K- 07 20 03 12	0 - 1.0 bar	160.0	G 1/2"
K- 07 20 03 13	0 - 10.0 bar	160.0	G 1/2"
K- 07 20 03 14	0 - 16.0 bar	160.0	G 1/2"
K- 07 20 03 15	0 - 25.0 bar	160.0	G 1/2"