


Pressure gauge stopcocks, male - female/female



Izmantošana

For all pressure gauges with a flat gasket acc. to DIN 16258

Spiediena diapazons

Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures

Temperatūra

Max. +50 °C

Korpuss

Brass with a bare metal surface or stainless steel 1.4571

Rokturis

Plastic

Pārbaudes atloks

-

## Apraksts

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Materiāls	PN (bar)	SW mm	Vītnes
K- 07 20 11 27	Misiņš	6	17	G 1/4
K- 07 20 11 29	Misiņš	25	27	G 1/2
K- 07 20 11 28	Nerūsējošais tērauds	25	27	G 1/2
K- 07 20 11 31	Misiņš	25	27	G 1/2
K- 07 20 11 30	Nerūsējošais tērauds	25	27	G 1/2
K- 07 20 11 32	Misiņš	25	27	G 1/2