

Standard pressure gauges with black sheet-steel bezel, connection on rear



Tips

111.12

Izmantošana

gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise

Modelis

Bourdon-tube pressure gauge, standard design, mounting ring

Chromium plated sheet steel

Steel chrome plated or black or with triangular bezel

Kvalitātes klase

1,6

Vides temperatūra

no -20 °C līdz +60 °C

Vielas temperatūra

maks. +60 °C

Korpuss

Sheet steel

Mērelementa un rādītāja materiāls

Vara sakausējums

Skatstikls

Transparent plastic

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 04 27	-1 / 0.0 bar	40.0	G 1/8"
K- 07 20 04 28	0 - 1.0 bar	40.0	G 1/8"
K- 07 20 04 29	0 - 1.6 bar	40.0	G 1/8"
K- 07 20 04 30	0 - 2.5 bar	40.0	G 1/8"
K- 07 20 04 31	0 - 4.0 bar	40.0	G 1/8"
K- 07 20 04 32	0 - 6.0 bar	40.0	G 1/8"
K- 07 20 04 33	0 - 10.0 bar	40.0	G 1/8"
K- 07 20 04 34	0 - 16.0 bar	40.0	G 1/8"
K- 07 20 04 35	0 - 25.0 bar	40.0	G 1/8"
K- 07 20 04 36	0 - 40.0 bar	40.0	G 1/8"
K- 07 20 05 30	-1 / 0.0 bar	50.0	G 1/4"
K- 07 20 05 31	0 - 1.0 bar	50.0	G 1/4"
K- 07 20 05 32	0 - 1.6 bar	50.0	G 1/4"
K- 07 20 05 33	0 - 2.5 bar	50.0	G 1/4"
K- 07 20 05 34	0 - 4.0 bar	50.0	G 1/4"
K- 07 20 05 35	0 - 6.0 bar	50.0	G 1/4"
K- 07 20 05 36	0 - 10.0 bar	50.0	G 1/4"
K- 07 20 05 37	0 - 16.0 bar	50.0	G 1/4"
K- 07 20 05 38	0 - 25.0 bar	50.0	G 1/4"
K- 07 20 05 39	0 - 40.0 bar	50.0	G 1/4"
K- 07 20 05 40	0 - 60.0 bar	50.0	G 1/4"