



Modelis  
90° caurules līkums  
Standarts  
DIN 2391/C  
Materiāls  
Tērauds ST 37.4 NBK (1.0255)  
Virsmas aizsardzība  
fosfatēts un ieeļlots

## Apraksts

Seamless pipe bends 90° for minimum loss of flow.

## Produkts

Apzīmējums	Caurules ārējais Ø mm	Iekšējais Ø nom. mm	S mm	Liekuma rādiuss R mm	a mm	b mm	L1 mm	L2 mm
RB 14-1.5	14.0	11.0	1.50	30	200.0	40.0	230.0	70.0
RB 15-1.5	15.0	12.0	1.50	30	200.0	40.0	230.0	70.0
RB 15-2	15.0	11.0	2.00	30	200.0	40.0	230.0	70.0
RB 16-2	16.0	12.0	2.00	30	200.0	40.0	230.0	70.0
RB 18-1.5	18.0	15.0	1.50	36	200.0	35.0	236.0	71.0
RB 18-2	18.0	14.0	2.00	36	200.0	35.0	236.0	72.0
RB 20-2	20.0	16.0	2.00	36	200.0	45.0	236.0	81.0
RB 20-2.5	20.0	15.0	2.50	36	200.0	45.0	236.0	81.0
RB 20-3	20.0	14.0	3.00	36	200.0	45.0	236.0	81.0
RB 22-1.5	22.0	19.0	1.50	38	200.0	40.0	238.0	78.0
RB 22-2	22.0	18.0	2.00	38	200.0	40.0	238.0	78.0
RB 22-2.5	22.0	17.0	2.50	38	200.0	40.0	238.0	78.0
RB 22-3.5	22.0	15.0	3.50	38	200.0	40.0	238.0	78.0
RB 25-2	25.0	21.0	2.00	44	200.0	50.0	244.0	94.0
RB 25-2.5	25.0	20.0	2.50	44	200.0	50.0	244.0	94.0
RB 25-3	25.0	19.0	3.00	44	200.0	50.0	244.0	94.0
RB 25-4	25.0	17.0	4.00	44	200.0	50.0	244.0	94.0
RB 28-1.5	28.0	25.0	1.50	48	200.0	50.0	248.0	98.0
RB 28-2	28.0	24.0	2.00	48	200.0	50.0	248.0	98.0
RB 28-3	28.0	22.0	3.00	48	200.0	50.0	248.0	98.0
RB 30-2.5	30.0	25.0	2.50	50	200.0	60.0	250.0	110.0
RB 30-3	30.0	24.0	3.00	50	200.0	60.0	250.0	110.0
RB 30-4	30.0	22.0	4.00	50	200.0	60.0	250.0	110.0
RB 35-2	35.0	31.0	2.00	60	200.0	65.0	260.0	125.0
RB 35-3	35.0	29.0	3.00	60	200.0	65.0	260.0	125.0
RB 38-2.5	38.0	33.0	2.50	65	200.0	75.0	265.0	140.0
RB 38-3	38.0	32.0	3.00	65	200.0	75.0	265.0	140.0
RB 38-4	38.0	30.0	4.00	65	200.0	75.0	265.0	140.0
RB 38-5	38.0	28.0	5.00	65	200.0	75.0	265.0	140.0
RB 42-2	42.0	38.0	2.00	80	200.0	85.0	280.0	165.0
RB 42-3	42.0	36.0	3.00	80	200.0	85.0	280.0	165.0
RB 50-6	50.0	38.0	6.00	210	100.0	100.0	310.0	310.0
RB 65-8	65.0	49.0	8.00	210	110.0	110.0	320.0	320.0
RB 80-10	80.0	60.0	10.00	150	120.0	120.0	330.0	330.0