



Ekspluatācijas temperatūra

-60 °C to +100 °C (PA 12)

Īpašības

Resistant to corrosion, vibration, impact, ageing, high pressures and heat

Materiāls

Polyamid PA 12, hard (according to DIN 73378)

Apraksts

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For \varnothing 12 mm to \varnothing 32 mm pipe systems and for \varnothing 4 mm to \varnothing 12 mm pneumatic applications

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	\varnothing šļūtenei iekšpusē mm	\varnothing šļūtenei ārpusē mm	maks. ekspluatācijas spiediens pie 20 °C bar	Ru_a garums m
K- 07 10 04 77	9.0	12.0	19	25
K- 07 10 04 79	12.0	15.0	15	25
K- 07 10 04 81	14.0	18.0	16	25
K- 07 10 04 83	18.0	22.0	14	25
K- 07 10 04 76	9.0	12.0	19	100
K- 07 10 04 78	12.0	15.0	15	100
K- 07 10 04 80	14.0	18.0	16	100
K- 07 10 04 82	18.0	22.0	14	100
K- 07 10 04 84	23.0	28.0	14	50