

K-ROHRDOPPELNIPPEL 23 AG ST37

VZ

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982



Darba spiediens
Max. 50 bar
Virsmā
Hot dip galvanised
Pieslēguma vītne
acc. ISO 7-1
Materiāls
Zinc plated steel ST 37-2

Apraksts

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Garums mm
K- 07 40 35 71	R 1/4	40.0
K- 07 40 35 72	R 1/4	60.0
K- 07 40 35 73	R 1/4	80.0
K- 07 40 35 66	R 1/4	100.0
K- 07 40 35 67	R 1/4	120.0
K- 07 40 35 68	R 1/4	150.0
K- 07 40 35 69	R 1/4	180.0
K- 07 40 35 70	R 1/4	200.0
K- 07 40 35 95	R 3/8	40.0
K- 07 40 35 96	R 3/8	60.0
K- 07 40 35 97	R 3/8	80.0
K- 07 40 35 90	R 3/8	100.0
K- 07 40 35 91	R 3/8	120.0
K- 07 40 35 92	R 3/8	150.0
K- 07 40 35 93	R 3/8	180.0
K- 07 40 35 94	R 3/8	200.0
K- 07 40 35 63	R 1/2	40.0
K- 07 40 35 64	R 1/2	60.0
K- 07 40 35 65	R 1/2	80.0
K- 07 40 35 58	R 1/2	100.0
K- 07 40 35 59	R 1/2	120.0
K- 07 40 35 60	R 1/2	150.0
K- 07 40 35 61	R 1/2	180.0
K- 07 40 35 62	R 1/2	200.0
K- 07 40 35 87	R 3/4	40.0
K- 07 40 35 88	R 3/4	60.0
K- 07 40 35 89	R 3/4	80.0
K- 07 40 35 82	R 3/4	100.0
K- 07 40 35 83	R 3/4	120.0
K- 07 40 35 84	R 3/4	150.0
K- 07 40 35 85	R 3/4	180.0
K- 07 40 35 86	R 3/4	200.0

Apzīmējums	Vitnes	Garums mm
K- 07 40 35 39	R 1	40.0
K- 07 40 35 40	R 1	60.0
K- 07 40 35 41	R 1	80.0
K- 07 40 35 34	R 1	100.0
K- 07 40 35 35	R 1	120.0
K- 07 40 35 36	R 1	150.0
K- 07 40 35 37	R 1	180.0
K- 07 40 35 38	R 1	200.0
K- 07 40 35 55	R 1 1/4	40.0
K- 07 40 35 56	R 1 1/4	60.0
K- 07 40 35 57	R 1 1/4	80.0
K- 07 40 35 50	R 1 1/4	100.0
K- 07 40 35 51	R 1 1/4	120.0
K- 07 40 35 52	R 1 1/4	150.0
K- 07 40 35 53	R 1 1/4	180.0
K- 07 40 35 54	R 1 1/4	200.0
K- 07 40 35 47	R 1 1/2	40.0
K- 07 40 35 48	R 1 1/2	60.0
K- 07 40 35 49	R 1 1/2	80.0
K- 07 40 35 42	R 1 1/2	100.0
K- 07 40 35 43	R 1 1/2	120.0
K- 07 40 35 44	R 1 1/2	150.0
K- 07 40 35 45	R 1 1/2	180.0
K- 07 40 35 46	R 1 1/2	200.0
K- 07 40 35 79	R 2	40.0
K- 07 40 35 80	R 2	60.0
K- 07 40 35 81	R 2	80.0
K- 07 40 35 74	R 2	100.0
K- 07 40 35 75	R 2	120.0
K- 07 40 35 76	R 2	150.0
K- 07 40 35 77	R 2	180.0
K- 07 40 35 78	R 2	200.0
K- 07 40 50 93	R 2 1/2	80.0
K- 07 40 50 88	R 2 1/2	100.0
K- 07 40 50 89	R 2 1/2	120.0
K- 07 40 50 90	R 2 1/2	150.0
K- 07 40 50 91	R 2 1/2	180.0
K- 07 40 50 92	R 2 1/2	200.0
K- 07 40 50 99	R 3	80.0
K- 07 40 50 94	R 3	100.0
K- 07 40 50 95	R 3	120.0
K- 07 40 50 96	R 3	150.0
K- 07 40 50 97	R 3	180.0
K- 07 40 50 98	R 3	200.0