

K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continuous thread



Darba spiediens
Max. 50 bar
Pieslēguma vītne
acc. ISO 7-1
Materiāls
black steel ST 37-2

Apraksts

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Garums mm |
|----------------|---------|--------------|
| K- 07 40 35 30 | R 1/4 | 25.0 |
| K- 07 40 35 33 | R 3/8 | 26.0 |
| K- 07 40 35 29 | R 1/2 | 34.0 |
| K- 07 40 35 32 | R 3/4 | 36.0 |
| K- 07 40 35 26 | R 1 | 43.0 |
| K- 07 40 35 28 | R 1 1/4 | 48.0 |
| K- 07 40 35 27 | R 1 1/2 | 48.0 |
| K- 07 40 35 31 | R 2 | 56.0 |
| K- 07 40 50 36 | R 2 1/2 | 65.0 |
| K- 07 40 50 37 | R 3 | 71.0 |