


K-RED FLANSCH 80-100 IG INFI

Reducing flange Ø 80 mm/Ø 110 mm with female thread



Darba vides
Compressed air, vacuum, inert gases
Eksploatācijas spiediens
-0,99 bar - 15 bar
Temperatūras diapazons
-20 °C to +80 °C
Blīvgredzens
NBR
Drošības gredzens
Technopolymer
Iedobes skrūve
Galvanised steel
Korpuss
Aluminium, treated surface
paškontrējošs uzgrieznis
Galvanised steel
Spīlgredzens
Stainless steel 1.4301
Uzgrieznis
Aluminium, surface treated
Vadgredzens
Technopolymer

Produkts

Apzīmējums	caurules ārējam Ø mm	Savienojums	A mm	L mm	SW mm
K- 07 40 55 23	80	G 3/4"	14.5	42.0	42
K- 07 40 55 24	80	G 1"	17.0	42.0	49
K- 07 40 55 25	80	G 1 1/2	20.0	42.0	66
K- 07 40 55 26	80	G 2"	22.0	42.0	80
K- 07 40 54 73	110	G 3/4"	14.5	48.0	42
K- 07 40 54 74	110	G 1"	17.0	48.0	49
K- 07 40 54 75	110	G 1 1/2	20.0	48.0	66
K- 07 40 54 76	110	G 2"	22.0	48.0	80