

# K-RD MUFFE RUND

Reducing sockets, round

# HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens  
Max. 20 bar  
Iekšējā vītne  
Parallel to DIN EN ISO 228-1  
Materiāls  
Stainless steel 1.4408

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	L1 mm	Vītne 1 iekšpusē	Vītne 2 iekšpusē
K- 07 40 14 73	27.0	G 1/4	G 1/8
K- 07 40 14 74	28.4	G 3/8	G 1/8
K- 07 40 14 75	29.5	G 3/8	G 1/4
K- 07 40 45 80	32.0	G 1/2	G 1/8
K- 07 40 14 76	32.0	G 1/2	G 1/4
K- 07 40 14 77	33.5	G 1/2	G 3/8
K- 07 40 14 78	36.0	G 3/4	G 3/8
K- 07 40 14 79	38.5	G 3/4	G 1/2
K- 07 40 45 81	38.8	G 1	G 3/8
K- 07 40 14 80	40.5	G 1	G 1/2
K- 07 40 14 81	41.5	G 1	G 3/4
K- 07 40 45 82	43.5	G 1 1/4	G 1/2
K- 07 40 14 82	45.0	G 1 1/4	G 3/4
K- 07 40 14 83	48.0	G 1 1/4	G 1
K- 07 40 45 83	47.5	G 1 1/2	G 3/4
K- 07 40 14 84	54.1	G 1 1/2	G 1
K- 07 40 14 85	54.0	G 1 1/2	G 1 1/4
K- 07 40 14 86	54.0	G 2	G 1
K- 07 40 45 84	57.0	G 2	G 1 1/4
K- 07 40 14 87	56.0	G 2	G 1 1/2