


# K-XV RD 6-KANT

Double nipples, unequal, hexagonal



Darba spiediens  
Max. 20 bar  
Ārējā vītne  
Parallel to DIN EN ISO 228-1  
Materiāls  
Stainless steel 1.4408

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	L1 mm	L2 mm	SW	Vītne 1 ārpusē	Vītne 2 ārpusē
K- 07 40 12 27	30.4	11.0	15 mm	G 1/4	G 1/8
K- 07 40 12 28	34.2	12.0	20 mm	G 3/8	G 1/8
K- 07 40 12 29	35.8	12.8	20 mm	G 3/8	G 1/4
K- 07 40 12 30	38.0	13.0	24 mm	G 1/2	G 1/4
K- 07 40 12 31	40.0	15.0	24 mm	G 1/2	G 3/8
K- 07 40 12 32	41.0	16.0	27 mm	G 3/4	G 3/8
K- 07 40 12 33	42.9	16.0	29 mm	G 3/4	G 1/2
K- 07 40 12 34	46.0	17.0	36 mm	G 1	G 1/2
K- 07 40 12 35	46.0	16.5	36 mm	G 1	G 3/4
K- 07 40 12 36	50.0	17.5	45 mm	G 1 1/4	G 3/4
K- 07 40 12 37	51.0	18.5	45 mm	G 1 1/4	G 1
K- 07 40 12 38	52.0	18.5	51 mm	G 1 1/2	G 1
K- 07 40 12 39	55.0	20.7	51 mm	G 1 1/2	G 1 1/4
K- 07 40 12 40	58.0	20.0	62 mm	G 2	G 1
K- 07 40 12 41	60.0	21.5	63 mm	G 2	G 1 1/2