


Ring nipples, single



Impulsu darba spiediens
Max. 10 bar
piemērots caurules materiāls
PVDF, PTFE, stainless steel, PA, PU
Spiediens
Max. 15 bar (depending on pipe quality)
Standarts
G thread acc. to DIN EN ISO 228-1
Vides temperatūra
-20 °C to max. +150 °C (depending on pipe quality and diameter)
Materiāls
Nerūsējošais tērauds 1.4404
Blīvējums
FKM

Apraksts

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	Šļūtenes ārējais Ø
K- 07 40 47 10	G 1/8	19.5	15.0	4 mm
K- 07 40 47 11	G 1/8	22.0	15.0	6 mm
K- 07 40 47 12	G 1/8	22.5	15.0	8 mm
K- 07 40 47 08	G 1/4	23.5	17.0	6 mm
K- 07 40 47 09	G 1/4	24.0	17.0	8 mm
K- 07 40 47 07	G 1/4	27.0	17.0	10 mm
K- 07 40 47 13	G 3/8	29.0	20.0	10 mm
K- 07 40 47 14	G 3/8	31.0	20.0	12 mm
K- 07 40 47 06	G 1/2	33.0	24.0	12 mm