


Ring nipples, single



Impulsu darba spiediens  
Max. 10 bar  
piemērots caurules materiāls  
PVDF, PTFE, stainless steel, PA, PU  
Spiediens  
Max. 15 bar (depending on pipe quality)  
Standarts  
G thread acc. to DIN EN ISO 228-1  
Vides temperatūra  
-20 °C to max. +150 °C (depending on pipe quality and diameter)  
Materiāls  
Nerūsējošais tērauds 1.4404  
Blīvējums  
FKM

## Apraksts

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø
K- 07 40 47 10	G 1/8	19.5	15.0	4 mm
K- 07 40 47 11	G 1/8	22.0	15.0	6 mm
K- 07 40 47 12	G 1/8	22.5	15.0	8 mm
K- 07 40 47 08	G 1/4	23.5	17.0	6 mm
K- 07 40 47 09	G 1/4	24.0	17.0	8 mm
K- 07 40 47 07	G 1/4	27.0	17.0	10 mm
K- 07 40 47 13	G 3/8	29.0	20.0	10 mm
K- 07 40 47 14	G 3/8	31.0	20.0	12 mm
K- 07 40 47 06	G 1/2	33.0	24.0	12 mm