

# K-L-STECKVER DREH AG-K VA

Male elbows, swivel type, conical male thread



Impulsu darba spiediens  
Max. 10 bar  
piemērots caurules materiāls  
PVDF, PTFE, stainless steel, PA, PU  
Spiediens  
Max. 15 bar (depending on pipe quality)  
Standarts  
R thread acc. to ISO 7-1  
Vides temperatūra  
-20 °C to max. +150 °C (depending on pipe quality and diameter)  
Materiāls  
Nerūsējošais tērauds 1.4404  
Blīvējums  
FKM

## Apraksts

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø	SW
K- 07 40 24 44	R 1/8	17.0	17.5	4 mm	10 mm
K- 07 40 24 45	R 1/8	21.5	20.0	6 mm	13 mm
K- 07 40 24 46	R 1/8	22.0	20.0	8 mm	13 mm
K- 07 40 24 42	R 1/4	21.5	24.0	6 mm	14 mm
K- 07 40 24 43	R 1/4	22.0	24.0	8 mm	14 mm
K- 07 40 24 41	R 1/4	25.5	26.5	10 mm	16 mm
K- 07 40 24 47	R 3/8	25.5	27.0	10 mm	17 mm
K- 07 40 24 48	R 3/8	28.0	30.5	12 mm	22 mm
K- 07 40 24 40	R 1/2	28.0	33.5	12 mm	22 mm