

K-RD NIPPEL KURZ ES

Reducing nipples, short type



Darba spiediens
Max. 20 bar
Materiāls
Nerūsējošais tērauds 1.4571

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Iekšējā vītne	Ārējā vītne	L1 mm	L2 mm	SW
K- 07 40 15 27	M 5	G 1/8	11.0	7.0	14 mm
K- 07 40 15 26	M 5	G 1/4	14.0	10.0	17 mm
K- 07 40 15 28	G 1/8	G 1/4	13.0	8.0	17 mm
K- 07 40 15 33	G 1/8	G 3/8	13.0	9.5	19 mm
K- 07 40 15 29	G 1/4	G 3/8	13.0	9.5	19 mm
K- 07 40 15 35	G 1/8	G 1/2	18.0	12.0	24 mm
K- 07 40 15 34	G 1/4	G 1/2	15.5	11.5	22 mm
K- 07 40 15 30	G 3/8	G 1/2	15.5	11.5	22 mm
K- 07 40 15 36	G 3/8	G 3/4	18.0	12.0	32 mm
K- 07 40 15 31	G 1/2	G 3/4	21.0	14.0	32 mm
K- 07 40 15 37	G 1/2	G 1	24.0	16.0	36 mm
K- 07 40 15 32	G 3/4	G 1	18.0	12.0	36 mm