


# K-RD NIPPEL LANG ES

Reducing nipples, long type

**HANSA FLEX**  
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens  
Max. 20 bar  
Materiāls  
Nerūsējošais tērauds 1.4571

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Iekšējā vītne	Ārējā vītne	L1 mm	L2 mm	SW
K- 07 40 15 38	M 5	M 5	16.0	5.5	10 mm
K- 07 40 15 39	G 1/8	M 5	17.0	5.0	14 mm
K- 07 40 15 43	G 1/8	G 1/8	23.0	8.0	14 mm
K- 07 40 15 40	G 1/4	G 1/8	26.0	10.0	17 mm
K- 07 40 15 44	G 1/8	G 1/4	28.0	10.0	17 mm
K- 07 40 15 45	G 1/4	G 1/4	28.0	10.0	17 mm
K- 07 40 15 41	G 3/8	G 1/4	26.0	10.0	19 mm
K- 07 40 15 46	G 1/4	G 3/8	29.0	10.0	19 mm
K- 07 40 15 47	G 3/8	G 3/8	29.0	10.0	19 mm
K- 07 40 15 42	G 1/2	G 3/8	27.0	12.0	24 mm
K- 07 40 15 48	G 3/8	G 1/2	34.0	12.0	24 mm
K- 07 40 15 49	G 1/2	G 1/2	34.0	12.0	24 mm
K- 07 40 15 50	G 3/4	G 1/2	38.0	13.0	32 mm