



Darba spiediens
Max. 20 bar
Materiāls
Nerūsējošais tērauds 1.4571

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | uzmavuzgrieznim | šļūtenei | SW |
|----------------|--------|----------|----------|-----------------|----------|-------|
| K- 07 40 13 30 | G 1/8 | 35.0 | 10.0 | LW 6 mm | LW 6 mm | 12 mm |
| K- 07 40 13 31 | G 1/8 | 35.0 | 10.0 | LW 8 mm | LW 8 mm | 12 mm |
| K- 07 40 13 32 | G 1/4 | 36.0 | 11.0 | LW 6 mm | LW 6 mm | 17 mm |
| K- 07 40 13 33 | G 1/4 | 36.0 | 11.0 | LW 8 mm | LW 8 mm | 17 mm |
| K- 07 40 13 34 | G 1/4 | 36.0 | 11.0 | LW 10 mm | LW 10 mm | 17 mm |
| K- 07 40 13 35 | G 1/4 | 40.5 | 11.0 | LW 13 mm | LW 13 mm | 17 mm |
| K- 07 40 13 36 | G 3/8 | 36.0 | 11.0 | LW 6 mm | LW 6 mm | 19 mm |
| K- 07 40 13 37 | G 3/8 | 36.0 | 11.0 | LW 8 mm | LW 8 mm | 19 mm |
| K- 07 40 13 38 | G 3/8 | 36.0 | 11.0 | LW 10 mm | LW 10 mm | 19 mm |
| K- 07 40 13 39 | G 3/8 | 40.5 | 11.0 | LW 13 mm | LW 13 mm | 19 mm |
| K- 07 40 13 40 | G 1/2 | 39.0 | 14.5 | LW 6 mm | LW 6 mm | 24 mm |
| K- 07 40 13 41 | G 1/2 | 39.0 | 14.5 | LW 8 mm | LW 8 mm | 24 mm |
| K- 07 40 13 42 | G 1/2 | 39.0 | 14.5 | LW 10 mm | LW 10 mm | 24 mm |
| K- 07 40 13 43 | G 1/2 | 44.0 | 14.5 | LW 13 mm | LW 13 mm | 24 mm |