



Darba spiediens
Max. 20 bar
Materiāls
Nerūsējošais tērauds 1.4571

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	uzmavuzgrieznim	šļūtenei	SW
K- 07 40 13 30	G 1/8	35.0	10.0	LW 6 mm	LW 6 mm	12 mm
K- 07 40 13 31	G 1/8	35.0	10.0	LW 8 mm	LW 8 mm	12 mm
K- 07 40 13 32	G 1/4	36.0	11.0	LW 6 mm	LW 6 mm	17 mm
K- 07 40 13 33	G 1/4	36.0	11.0	LW 8 mm	LW 8 mm	17 mm
K- 07 40 13 34	G 1/4	36.0	11.0	LW 10 mm	LW 10 mm	17 mm
K- 07 40 13 35	G 1/4	40.5	11.0	LW 13 mm	LW 13 mm	17 mm
K- 07 40 13 36	G 3/8	36.0	11.0	LW 6 mm	LW 6 mm	19 mm
K- 07 40 13 37	G 3/8	36.0	11.0	LW 8 mm	LW 8 mm	19 mm
K- 07 40 13 38	G 3/8	36.0	11.0	LW 10 mm	LW 10 mm	19 mm
K- 07 40 13 39	G 3/8	40.5	11.0	LW 13 mm	LW 13 mm	19 mm
K- 07 40 13 40	G 1/2	39.0	14.5	LW 6 mm	LW 6 mm	24 mm
K- 07 40 13 41	G 1/2	39.0	14.5	LW 8 mm	LW 8 mm	24 mm
K- 07 40 13 42	G 1/2	39.0	14.5	LW 10 mm	LW 10 mm	24 mm
K- 07 40 13 43	G 1/2	44.0	14.5	LW 13 mm	LW 13 mm	24 mm