

K-T-STECK VERS DRE AG OR VA

Male branch tees, swivel type, parallel male thread with O-ring



Impulsu darba spiediens
Max. 10 bar
piemērots caurules materiāls
PVDF, PTFE, stainless steel, PA, PU
Spiediens
Max. 15 bar (depending on pipe quality)
Standarts
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring
Vides temperatūra
-20 °C to max. +150 °C (depending on pipe quality and diameter)
Materiāls
Nerūsējošais tērauds 1.4404
Blīvējums
FKM

Apraksts

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējais Ø	SW
K- 07 40 46 81	M 5	34.0	18.0	4 mm	9 mm
K- 07 40 24 52	G 1/8	34.0	20.0	4 mm	13 mm
K- 07 40 24 53	G 1/8	42.0	22.5	6 mm	13 mm
K- 07 40 24 54	G 1/8	43.0	22.5	8 mm	13 mm
K- 07 40 24 50	G 1/4	42.0	24.5	6 mm	16 mm
K- 07 40 24 51	G 1/4	43.0	24.5	8 mm	16 mm
K- 07 40 24 49	G 1/4	50.0	25.5	10 mm	16 mm
K- 07 40 24 55	G 3/8	50.0	27.0	10 mm	21 mm