



Ekspluatācijas temperatūra  
-20 °C to +70 °C in air; +1 °C to +70 °C in water  
Blīvējums  
NBR  
Materiāls  
Acetalpolymerisat (POM)  
Darba spiediens  
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

## Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Īscaurule mm	Šļūtenes ārējais Ø	L1 mm
K- 07 40 28 91	12	8 mm	46.7
K- 07 40 28 92	12	10 mm	50.9
K- 07 40 28 93	15	10 mm	61.2
K- 07 40 28 94	15	12 mm	61.2
K- 07 40 28 95	18	15 mm	71.7
K- 07 40 28 96	22	15 mm	72.7
K- 07 40 28 97	22	18 mm	71.8
K- 07 40 28 98	28	15 mm	81.4
K- 07 40 28 99	28	22 mm	82.6