



Ekspluatācijas temperatūra  
-20 °C to +70 °C in air; +1 °C to +70 °C in water  
Blīvējums  
NBR  
Materiāls  
Acetalpolymerisat (POM)  
Darba spiediens  
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

## Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Šļūtenes ārējais Ø	L1 mm
K- 07 40 28 41	4 mm	33.6
K- 07 40 28 42	5 mm	34.6
K- 07 40 28 43	6 mm	36.9
K- 07 40 28 44	8 mm	40.0
K- 07 40 28 45	10 mm	43.9
K- 07 40 28 46	12 mm	55.8
K- 07 40 28 47	15 mm	62.0
K- 07 40 28 48	18 mm	66.5
K- 07 40 28 49	22 mm	72.2
K- 07 40 28 50	28 mm	95.6