



Ekspluatācijas temperatūra
-20 °C to +70 °C in air; +1 °C to +70 °C in water
Blīvējums
NBR
Materiāls
Acetalpolymerisat (POM)
Darba spiediens
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Īscaurule mm	L1 mm	Krāsa
K- 07 40 29 11	4	28.0	sarkans
K- 07 40 29 12	5	28.0	sarkans
K- 07 40 29 13	6	30.0	sarkans
K- 07 40 29 14	8	31.0	sarkans
K- 07 40 29 15	10	36.5	sarkans
K- 07 40 29 16	12	38.5	sarkans
K- 07 40 29 17	15	45.0	melns
K- 07 40 29 18	18	41.5	melns
K- 07 40 29 19	22	45.0	melns
K- 07 40 29 20	28	56.0	melns