



Ekspluatācijas temperatūra
-20 °C to +70 °C in air; +1 °C to +70 °C in water
Blīvējums
NBR
Materiāls
Acetalpolymerisat (POM)
Darba spiediens
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Īscaurule mm	Šļūtenes ārējais Ø	L1 mm	L2 mm
K- 07 40 29 02	4	4 mm	22.8	27.3
K- 07 40 29 03	5	5 mm	22.8	27.3
K- 07 40 29 04	6	6 mm	25.9	30.8
K- 07 40 29 05	8	8 mm	28.4	34.4
K- 07 40 29 06	10	10 mm	32.7	38.8
K- 07 40 29 07	12	12 mm	42.3	48.5
K- 07 40 29 08	15	15 mm	50.7	57.9
K- 07 40 29 09	18	18 mm	54.2	62.1