

K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Ekspluatācijas spiediens
Max. 15 bar
MS vītnes griezes moments
12 Nm
Stiprinājuma griezes moments
4 Nm
Temperatūras diapazons
-10 °C to +50 °C
Korpuss
Glass fibre-reinforced plastic
Vītne
Brass

Apraksts

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ieejas vītnes	Savienojošās vītnes
K- 07 40 48 12	G 1/2"	1 x G 1/2
K- 07 40 48 13	G 1/2"	2 x G 1/2
K- 07 40 48 14	G 1/2"	3 x G 1/2
K- 07 40 48 15	G 3/4"	1 x G 1/2
K- 07 40 48 16	G 3/4"	2 x G 1/2
K- 07 40 48 17	G 3/4"	3 x G 1/2