

K-DRV ABLD RAENDEL DREH OR

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVniecība

Unidirectional flow control valves with outgoing air restriction, adjustable with knurled screw, angled, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 15 bar, coarse vacuum
Darba vides
Compressed air and all gases or liquids that are compatible with the materials
ieteicamās šļūtenes
PU or PA (nylon)
Pieteikums platība
Air, vacuum
Temperatūras diapazons
-20 °C to +80 °C
Blīvēšanas virsma
Parallel version: O-ring in housing, Conical version: thread coating
Materiāls
Plastic, Nickel plated brass
Piespiedējgredzens
Plastic

Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	L1 mm	L2 min mm	šļūtenes ārējais Ø	L2 maks mm	SW
K- 07 40 07 56	M 5	20.0	29.0	4 mm	31.9	8 mm
K- 07 40 07 57	M 5	21.7	29.0	6 mm	31.9	8 mm
K- 07 40 07 67	G 1/8	22.3	37.8	4 mm	44.0	10 mm
K- 07 40 07 68	G 1/8	22.9	37.8	6 mm	44.0	10 mm
K- 07 40 07 69	G 1/8	25.3	37.8	8 mm	44.0	10 mm
K- 07 40 07 66	G 1/8	30.1	37.8	10 mm	44.0	10 mm
K- 07 40 07 63	G 1/4	24.0	44.0	4 mm	51.0	14 mm
K- 07 40 07 64	G 1/4	24.9	44.0	6 mm	51.0	14 mm
K- 07 40 07 65	G 1/4	28.4	44.0	8 mm	51.0	14 mm
K- 07 40 07 61	G 1/4	32.0	44.0	10 mm	51.0	14 mm
K- 07 40 07 62	G 1/4	32.0	44.0	12 mm	51.0	14 mm
K- 07 40 07 72	G 3/8	29.3	48.7	8 mm	55.0	19 mm
K- 07 40 07 70	G 3/8	32.5	48.7	10 mm	55.0	19 mm
K- 07 40 07 71	G 3/8	35.3	48.7	12 mm	55.0	19 mm
K- 07 40 07 60	G 1/2	32.3	53.0	8 mm	59.2	24 mm
K- 07 40 07 58	G 1/2	35.5	53.0	10 mm	59.2	24 mm
K- 07 40 07 59	G 1/2	36.3	53.0	12 mm	59.2	24 mm