


# K-DRV SCHLITZSCHR DREH BESCH

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNIECĪBA

Unidirectional flow control valves with outgoing air restriction, adjustable, angled, swivel type, parallel male thread with O-ring



Darba spiediens

Max. 10 bar

Darba vides

Compressed air and all gases or liquids that are compatible with the materials

ieteicamās šļūtenes

PU or PA (nylon)

Pieteikums platība

Air, vacuum

Temperatūras diapazons

-20 °C to +80 °C

Blīvēšanas virsma

Parallel version: O-ring in housing, Conical version: thread coating

Materiāls

Plastic, Nickel plated brass

Piespiedējgredzens

Plastic

## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 min mm	šļūtenes ārējais Ø	SW
K- 07 40 46 33	M 5	20.0	23.0	4 mm	8 mm
K- 07 40 46 34	M 5	21.5	23.0	6 mm	8 mm
K- 07 40 46 42	G 1/8	23.0	31.5	4 mm	12 mm
K- 07 40 46 43	G 1/8	23.0	31.5	6 mm	12 mm
K- 07 40 46 44	G 1/8	26.5	31.5	8 mm	12 mm
K- 07 40 46 39	G 1/4	25.0	38.3	4 mm	14 mm
K- 07 40 46 40	G 1/4	25.0	38.3	6 mm	14 mm
K- 07 40 46 41	G 1/4	29.0	38.3	8 mm	14 mm
K- 07 40 46 38	G 1/4	31.0	38.3	10 mm	14 mm
K- 07 40 46 47	G 3/8	27.0	43.0	6 mm	19 mm
K- 07 40 46 48	G 3/8	30.5	43.0	8 mm	19 mm
K- 07 40 46 45	G 3/8	32.0	43.0	10 mm	19 mm
K- 07 40 46 46	G 3/8	35.0	43.0	12 mm	19 mm
K- 07 40 46 37	G 1/2	33.0	49.0	8 mm	24 mm
K- 07 40 46 35	G 1/2	34.5	49.0	10 mm	24 mm
K- 07 40 46 36	G 1/2	36.5	49.0	12 mm	24 mm