

K-DRV AG-K STECK SCHL GEW

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVniecība

Unidirectional flow control valves with parallel male thread and plug connection, straight type, air restriction from tube to port



Darba spiediens

Max. 15 bar, coarse vacuum

Darba vides

Compressed air and all gases or liquids that are compatible with the materials
ieteicamās šļūtenes

PU or PA (nylon)

Pieteikums platība

Air, vacuum

Temperatūras diapazons

-20 °C to +80 °C

Blīvēšanas virsma

Parallel version: O-ring in housing, Conical version: thread coating

Materiāls

Plastic, Nickel plated brass

Piespiedējgredzens

Plastic

Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 min mm	šļūtenes ārējais Ø	L2 maks mm	SW
K- 07 40 06 99	G 1/8	46.5	28.9	4 mm	31.2	12 mm
K- 07 40 07 00	G 1/8	53.7	41.1	6 mm	46.8	14 mm
K- 07 40 07 01	G 1/8	58.1	41.7	8 mm	47.4	14 mm
K- 07 40 06 97	G 1/4	55.1	40.8	6 mm	47.0	14 mm
K- 07 40 06 98	G 1/4	59.6	44.8	8 mm	50.8	17 mm
K- 07 40 06 95	G 1/4	70.3	47.4	10 mm	54.0	17 mm
K- 07 40 06 96	G 1/4	80.6	50.3	12 mm	55.3	21 mm
K- 07 40 07 04	G 3/8	61.0	44.3	8 mm	50.4	17 mm
K- 07 40 07 02	G 3/8	71.6	48.5	10 mm	55.3	20 mm
K- 07 40 07 03	G 3/8	81.3	51.8	12 mm	57.1	21 mm
K- 07 40 06 93	G 1/2	76.0	48.3	10 mm	54.5	19 mm
K- 07 40 06 94	G 1/2	85.9	51.5	12 mm	56.8	24 mm