

# K-L-STECKVER ABSP DREH AG OR

Angle stop valves, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring  
Temperatūras diapazons  
0 °C to +60 °C  
Blīvēšanas virsma  
O-ring (NBR)  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union. &lt;br&gt;The flow rate is only guaranteed if the hose is securely inserted.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | L2<br>mm | šļūtenes ārējam Ø | SW    |
|----------------|--------|----------|----------|-------------------|-------|
| K- 07 40 08 46 | M 5    | 29.5     | 20.5     | 4 mm              | 10 mm |
| K- 07 40 08 47 | M 5    | 29.4     | 21.7     | 6 mm              | 12 mm |
| K- 07 40 08 40 | G 1/8  | 31.0     | 24.3     | 4 mm              | 14 mm |
| K- 07 40 08 41 | G 1/8  | 32.8     | 23.5     | 6 mm              | 14 mm |
| K- 07 40 08 42 | G 1/8  | 33.0     | 27.0     | 8 mm              | 14 mm |
| K- 07 40 08 38 | G 1/4  | 32.8     | 25.5     | 6 mm              | 17 mm |
| K- 07 40 08 39 | G 1/4  | 33.0     | 29.5     | 8 mm              | 17 mm |
| K- 07 40 08 37 | G 1/4  | 42.5     | 34.3     | 10 mm             | 17 mm |
| K- 07 40 08 45 | G 3/8  | 33.0     | 30.0     | 8 mm              | 20 mm |
| K- 07 40 08 43 | G 3/8  | 42.5     | 34.3     | 10 mm             | 20 mm |
| K- 07 40 08 44 | G 3/8  | 46.5     | 36.0     | 12 mm             | 21 mm |
| K- 07 40 08 35 | G 1/2  | 42.5     | 37.8     | 10 mm             | 24 mm |
| K- 07 40 08 36 | G 1/2  | 46.5     | 39.0     | 12 mm             | 24 mm |