

# K-L-STECKVER ABSP DREH AG OR

Angle stop valves, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring  
Temperatūras diapazons  
0 °C to +60 °C  
Blīvēšanas virsma  
O-ring (NBR)  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union. &lt;br&gt;The flow rate is only guaranteed if the hose is securely inserted.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 08 46	M 5	29.5	20.5	4 mm	10 mm
K- 07 40 08 47	M 5	29.4	21.7	6 mm	12 mm
K- 07 40 08 40	G 1/8	31.0	24.3	4 mm	14 mm
K- 07 40 08 41	G 1/8	32.8	23.5	6 mm	14 mm
K- 07 40 08 42	G 1/8	33.0	27.0	8 mm	14 mm
K- 07 40 08 38	G 1/4	32.8	25.5	6 mm	17 mm
K- 07 40 08 39	G 1/4	33.0	29.5	8 mm	17 mm
K- 07 40 08 37	G 1/4	42.5	34.3	10 mm	17 mm
K- 07 40 08 45	G 3/8	33.0	30.0	8 mm	20 mm
K- 07 40 08 43	G 3/8	42.5	34.3	10 mm	20 mm
K- 07 40 08 44	G 3/8	46.5	36.0	12 mm	21 mm
K- 07 40 08 35	G 1/2	42.5	37.8	10 mm	24 mm
K- 07 40 08 36	G 1/2	46.5	39.0	12 mm	24 mm