


Female bulkhead stop unions (pressure max. 10 bar)



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
M thread acc. to DIN 13-1, with O-Ring  
G thread acc. to DIN EN ISO 228-1, with O-Ring  
R thread acc. to ISO 7-1, thread coating  
Temperatūras diapazons  
0 °C to +60 °C  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union. &lt;br&gt;The flow rate is only guaranteed if the hose is securely inserted.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes     | L1<br>mm | šļūtenes ārējam Ø | SW    |
|----------------|------------|----------|-------------------|-------|
| K- 07 40 43 74 | M 12 x 1.5 | 41.0     | 4 mm              | 14 mm |
| K- 07 40 43 75 | M 14 x 1.5 | 44.5     | 6 mm              | 17 mm |
| K- 07 40 43 76 | M 16 x 1.5 | 50.3     | 8 mm              | 19 mm |
| K- 07 40 43 77 | M 20 x 1.5 | 58.5     | 10 mm             | 24 mm |
| K- 07 40 43 78 | M 24 x 1.5 | 62.2     | 12 mm             | 27 mm |