


# K-SCHOTT-STECKVERB ABSP

Female bulkhead stop unions (pressure max. 10 bar)



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
M thread acc. to DIN 13-1, with O-Ring  
G thread acc. to DIN EN ISO 228-1, with O-Ring  
R thread acc. to ISO 7-1, thread coating  
Temperatūras diapazons  
0 °C to +60 °C  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union. &lt;br&gt;The flow rate is only guaranteed if the hose is securely inserted.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	šļūtenes ārējais Ø	SW
K- 07 40 43 74	M 12 x 1.5	41.0	4 mm	14 mm
K- 07 40 43 75	M 14 x 1.5	44.5	6 mm	17 mm
K- 07 40 43 76	M 16 x 1.5	50.3	8 mm	19 mm
K- 07 40 43 77	M 20 x 1.5	58.5	10 mm	24 mm
K- 07 40 43 78	M 24 x 1.5	62.2	12 mm	27 mm