


# K-STECKVERSCHR ABSP AGR OR

Straight stop valves, parallel male thread with O-ring



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring  
Temperatūras diapazons  
0 °C to +60 °C  
Blīvēšanas virsma  
O-ring (NBR)  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union. &lt;br&gt;The flow rate is only guaranteed if the hose is securely inserted.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	šļūtenes ārējam Ø	SW
K- 07 40 08 18	G 1/8	27.5	4 mm	14 mm
K- 07 40 08 19	G 1/8	27.0	6 mm	14 mm
K- 07 40 08 20	G 1/8	29.0	8 mm	14 mm
K- 07 40 08 16	G 1/4	27.0	6 mm	17 mm
K- 07 40 08 17	G 1/4	31.9	8 mm	17 mm
K- 07 40 08 15	G 1/4	34.9	10 mm	17 mm
K- 07 40 08 23	G 3/8	31.9	8 mm	20 mm
K- 07 40 08 21	G 3/8	37.0	10 mm	20 mm
K- 07 40 08 22	G 3/8	38.0	12 mm	21 mm
K- 07 40 08 13	G 1/2	37.0	10 mm	24 mm
K- 07 40 08 14	G 1/2	38.0	12 mm	24 mm