


K-XRD STECKANSCHLUSS Z GEW

AGR-K BE

Straight non-return valves, flow direction from tube to port, conical male thread, coated



Darba spiediens
Max. 10 bar, vacuum
Darba vides
Saspiests gaiss
ieteicamās šļūtenes
PU or PA (nylon)
Pieteikums platība
Air, vacuum
Standarts
R-Gewinde nach ISO 7-1, Gewindebeschichtung
Temperatūras diapazons
0 °C to +60 °C
Blīvēšanas virsma
Conical version: thread coating
Materiāls
Plastic, Nickel plated brass
Piespiedējgredzens
Plastic

Apraksts

The non-return function of these push-in fittings prevents the air from flowing back. the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	S_kotn_jais spiediens nom. bar	šļūtenes ārējam Ø	SW
K- 07 40 08 97	R 1/8	24.0	0.2	4 mm	10 mm
K- 07 40 08 98	R 1/8	32.5	0.2	6 mm	12 mm
K- 07 40 08 99	R 1/8	32.8	0.2	8 mm	14 mm
K- 07 40 08 95	R 1/4	32.5	0.2	6 mm	14 mm
K- 07 40 08 96	R 1/4	37.2	0.2	8 mm	14 mm
K- 07 40 09 00	R 3/8	41.0	0.2	10 mm	17 mm
K- 07 40 09 01	R 3/8	42.5	0.2	12 mm	21 mm
K- 07 40 08 93	R 1/2	43.0	0.2	10 mm	21 mm
K- 07 40 08 94	R 1/2	44.5	0.2	12 mm	21 mm