


K-XRD STECKANSCHLUSS Z SCH AGR OR

Straight non-return valves, flow direction from port to tube, parallel male thread with O-ring



Darba spiediens
Max. 10 bar, vacuum
Darba vides
Saspiests gaiss
ieteicamās šļūtenes
PU or PA (nylon)
Pieteikums platība
Air, vacuum
Standarts
M thread acc. to DIN 13-1, with O-Ring
G thread acc. to DIN EN ISO 228-1, with O-Ring
R thread acc. to ISO 7-1, thread coating
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring
Temperatūras diapazons
0 °C to +60 °C
Blīvēšanas virsma
O-ring (NBR)
Materiāls
Plastic, Nickel plated brass
Piespiedējgredzens
Plastic

Apraksts

The non-return function of these push-in fittings prevents the air from flowing back. the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	L1 mm	S_kotn_jais spiediens nom. bar	šļūtenes ārējam Ø	SW
K- 07 40 08 73	M 5	31.0	0.2	4 mm	10 mm
K- 07 40 08 68	G 1/8	24.2	0.2	4 mm	14 mm
K- 07 40 08 69	G 1/8	32.5	0.2	6 mm	14 mm
K- 07 40 08 70	G 1/8	32.8	0.2	8 mm	14 mm
K- 07 40 08 66	G 1/4	33.0	0.2	6 mm	17 mm
K- 07 40 08 67	G 1/4	36.9	0.2	8 mm	17 mm
K- 07 40 08 71	G 3/8	41.0	0.2	10 mm	20 mm
K- 07 40 08 72	G 3/8	42.5	0.2	12 mm	21 mm
K- 07 40 08 64	G 1/2	43.0	0.2	10 mm	24 mm
K- 07 40 08 65	G 1/2	44.5	0.2	12 mm	24 mm