


# K-XRD STECKANSCHLUSS Z SCH AGR-K BE

Straight non-return valves, flow direction from port to tube, conical male thread, coated



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
R-Gewinde nach ISO 7-1, Gewindebeschichtung  
Temperatūras diapazons  
0 °C to +60 °C  
Blīvēšanas virsma  
Conical version: thread coating  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The non-return function of these push-in fittings prevents the air from flowing back. the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | S_kotn_jais<br>spiediens nom.<br>bar | šļūtenes ārējam Ø | SW    |
|----------------|--------|----------|--------------------------------------|-------------------|-------|
| K- 07 40 08 88 | R 1/8  | 27.3     | 0.2                                  | 4 mm              | 10 mm |
| K- 07 40 08 89 | R 1/8  | 32.5     | 0.2                                  | 6 mm              | 12 mm |
| K- 07 40 08 90 | R 1/8  | 32.8     | 0.2                                  | 8 mm              | 14 mm |
| K- 07 40 08 86 | R 1/4  | 33.0     | 0.2                                  | 6 mm              | 14 mm |
| K- 07 40 08 87 | R 1/4  | 34.8     | 0.2                                  | 8 mm              | 14 mm |
| K- 07 40 08 91 | R 3/8  | 41.0     | 0.2                                  | 10 mm             | 17 mm |
| K- 07 40 08 92 | R 3/8  | 42.5     | 0.2                                  | 12 mm             | 21 mm |
| K- 07 40 08 84 | R 1/2  | 43.0     | 0.2                                  | 10 mm             | 21 mm |
| K- 07 40 08 85 | R 1/2  | 44.5     | 0.2                                  | 12 mm             | 21 mm |