

# K-STECKVERBINDU RED 10BAR

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Reducers (pressure max. 10 bar)

Darba spiediens

Max. 10 bar

Darba vides

Compressed air and all gases or liquids that are compatible with the materials

ieteicamās šļūtenes

PU or PA (nylon)

Pieteikums platība

Air, vacuum

Temperatūras diapazons

-20 °C to +80 °C

Materiāls

Plastic, Nickel plated brass

Piespiedējgredzens

Plastic



## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	L1 mm	šļūtenes ārējam Ø
K- 07 40 03 45	31.0	6 mm / 4 mm
K- 07 40 41 34	36.5	8 mm / 4 mm
K- 07 40 03 46	34.5	8 mm / 6 mm
K- 07 40 41 35	40.2	10 mm / 6 mm
K- 07 40 03 47	39.4	10 mm / 8 mm
K- 07 40 41 36	45.0	12 mm / 8 mm
K- 07 40 03 48	44.2	12 mm / 10 mm
K- 07 40 03 49	49.6	16 mm / 12 mm