

# K-STECKVERSCHR AGR OR SK

Male connectors, parallel male thread with O-ring and outer hex

Darba spiediens

Max. 15 bar, coarse vacuum

Darba vides

Compressed air and all gases or liquids that are compatible with the materials

ieteicamās šļūtenes

PU or PA (nylon)

Pieteikums platība

Air, vacuum

Temperatūras diapazons

-20 °C to +80 °C

Blīvēšanas virsma


Parallel version: O-ring in housing

Materiāls

Plastic, Nickel plated brass

Piespiedējgredzens

Plastic



## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	Sešstūra iedobe mm	šļūtenes ārējam Ø	SW
K- 07 40 00 78	M 5	20.8	2.0	4 mm	10 mm
K- 07 40 00 79	M 5	22.2	2.0	6 mm	12 mm
K- 07 40 00 92	G 1/8	19.3	3.0	4 mm	10 mm
K- 07 40 00 93	G 1/8	20.2	4.0	6 mm	12 mm
K- 07 40 00 94	G 1/8	27.1	5.0	8 mm	14 mm
K- 07 40 00 90	G 1/8	28.9	5.0	10 mm	17 mm
K- 07 40 00 91	G 1/8	31.6	5.0	12 mm	21 mm
K- 07 40 00 87	G 1/4	17.4	3.0	4 mm	10 mm
K- 07 40 00 88	G 1/4	20.9	4.0	6 mm	12 mm
K- 07 40 00 89	G 1/4	23.0	6.0	8 mm	14 mm
K- 07 40 00 85	G 1/4	29.9	6.0	10 mm	17 mm
K- 07 40 00 86	G 1/4	32.6	6.0	12 mm	21 mm
K- 07 40 00 98	G 3/8	19.5	4.0	6 mm	12 mm
K- 07 40 00 99	G 3/8	22.1	6.0	8 mm	14 mm
K- 07 40 00 95	G 3/8	25.9	8.0	10 mm	17 mm
K- 07 40 00 96	G 3/8	28.6	8.0	12 mm	21 mm
K- 07 40 00 97	G 3/8	36.1	8.0	16 mm	24 mm
K- 07 40 00 83	G 1/2	22.6	4.0	6 mm	12 mm
K- 07 40 00 84	G 1/2	23.2	6.0	8 mm	14 mm
K- 07 40 00 80	G 1/2	24.5	8.0	10 mm	17 mm
K- 07 40 00 81	G 1/2	31.1	8.0	12 mm	21 mm
K- 07 40 00 82	G 1/2	38.1	10.0	16 mm	24 mm