


K-STECKVERSCHR AGR OR SK

Male connectors, parallel male thread with O-ring and outer hex



Darba spiediens
Max. 15 bar, coarse vacuum
Darba vides
Compressed air and all gases or liquids that are compatible with the materials
ieteicamās šļūtenes
PU or PA (nylon)
Pieteikums platība
Air, vacuum
Temperatūras diapazons
-20 °C to +80 °C
Blīvēšanas virsma
Parallel version: O-ring in housing
Materiāls
Plastic, Nickel plated brass
Piespiedējgredzens
Plastic

Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Sešstūra iedobe mm	šļūtenes ārējais Ø	SW
K- 07 40 00 78	M 5	20.8	2.0	4 mm	10 mm
K- 07 40 00 79	M 5	22.2	2.0	6 mm	12 mm
K- 07 40 00 92	G 1/8	19.3	3.0	4 mm	10 mm
K- 07 40 00 93	G 1/8	20.2	4.0	6 mm	12 mm
K- 07 40 00 94	G 1/8	27.1	5.0	8 mm	14 mm
K- 07 40 00 90	G 1/8	28.9	5.0	10 mm	17 mm
K- 07 40 00 91	G 1/8	31.6	5.0	12 mm	21 mm
K- 07 40 00 87	G 1/4	17.4	3.0	4 mm	10 mm
K- 07 40 00 88	G 1/4	20.9	4.0	6 mm	12 mm
K- 07 40 00 89	G 1/4	23.0	6.0	8 mm	14 mm
K- 07 40 00 85	G 1/4	29.9	6.0	10 mm	17 mm
K- 07 40 00 86	G 1/4	32.6	6.0	12 mm	21 mm
K- 07 40 00 98	G 3/8	19.5	4.0	6 mm	12 mm
K- 07 40 00 99	G 3/8	22.1	6.0	8 mm	14 mm
K- 07 40 00 95	G 3/8	25.9	8.0	10 mm	17 mm
K- 07 40 00 96	G 3/8	28.6	8.0	12 mm	21 mm
K- 07 40 00 97	G 3/8	36.1	8.0	16 mm	24 mm
K- 07 40 00 83	G 1/2	22.6	4.0	6 mm	12 mm
K- 07 40 00 84	G 1/2	23.2	6.0	8 mm	14 mm
K- 07 40 00 80	G 1/2	24.5	8.0	10 mm	17 mm
K- 07 40 00 81	G 1/2	31.1	8.0	12 mm	21 mm
K- 07 40 00 82	G 1/2	38.1	10.0	16 mm	24 mm