



Ekspluatācijas spiediens  
Max. 16 bar (at +20 °C)  
Ekspluatācijas temperatūra  
-20 °C to +70 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR, siliconefree  
Piespiedējgredzens  
Hostaform (black nickel-plated for Ø 10, 12)  
Spīlžoklis  
Stainless steel AISI 316

## Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø
K- 07 40 29 88	M 5	18.5	17.0	4 mm
K- 07 40 29 91	G 1/8	21.0	25.0	4 mm
K- 07 40 29 92	G 1/8	23.5	25.0	6 mm
K- 07 40 29 93	G 1/8	24.5	25.0	8 mm
K- 07 40 29 89	G 1/4	24.5	29.3	6 mm
K- 07 40 29 90	G 1/4	26.0	29.3	8 mm