



Ekspluatācijas spiediens  
Max. 16 bar (at +20 °C)  
Ekspluatācijas temperatūra  
-20 °C to +70 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR, siliconefree  
Piespiedējgredzens  
Hostaform (black nickel-plated for Ø 10, 12)  
Spīlžoklis  
Stainless steel AISI 316

## Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | L2<br>mm | Šļūtenes ārējam Ø | SW    |
|----------------|--------|----------|----------|-------------------|-------|
| K- 07 40 29 65 | R 1/8  | 16.1     | 17.5     | 4 mm              | 10 mm |
| K- 07 40 29 66 | R 1/8  | 20.0     | 17.5     | 6 mm              | 10 mm |
| K- 07 40 29 67 | R 1/8  | 24.0     | 18.5     | 8 mm              | 10 mm |
| K- 07 40 29 63 | R 1/4  | 23.0     | 22.0     | 6 mm              | 12 mm |
| K- 07 40 29 64 | R 1/4  | 24.0     | 22.0     | 8 mm              | 12 mm |
| K- 07 40 29 62 | R 1/4  | 24.0     | 22.0     | 10 mm             | 14 mm |